



The Application Specific Synthetic Papers

Mineral Filled Calendered Polypropylene Film - White Matte

HOP-SYN® Synthetic Paper



MANUFACTURING CAPABILITIES

THICKNESS	EMBOSSING	MASTER ROLL SPECS	CONVERTING
267 micron 10 mil	Matte/Matte	Up to 30" O.D. 55"	Slitting: Down to 1.5" Width Sheeting: 12"x18", 13"x19", 20.5" x 29.5"

FEATURES

- Indigo printable on any series Indigo (10000 model needs HP One Shot modification)
- Great for applications that require the durability of plastic.

PHYSICAL PROPERTIES

Mil	Micron	GSM	Embossing	Gravity	Yield	60%Gloss	Whiteness	Elongation	Tensile Strength	Roughness Standard 500kPa	Roughness Standard 1000kPa	Surface Resistivity
10.0	267	312	Matte/Matte	1.17	2404	6.2/19.7	80	300/60	3500/2000	4.66/1.76	3.16/1.60	10 ¹²



1251 Valley Brook Ave. Lyndhurst, NJ 07071 • Tel: 1-201-438-6200 • Fax: 1- 201-438-3833 • www.hopindustries.com

The information contained herein and recommended applications for use are for reference and comparison purposes only and to the best of our knowledge are accurate and reliable. Hop Industries Corporation makes no warranty regarding fitness for purpose of any product